



**Produktreihen**  
**H200-A/-B/-C/-D/-E**

**Fronteinbauschalter**

Antrieb nächster Baugröße

**Vierlochbefestigung**

48 x 48 mm

**013M1** (IP66)

Komplettschalter	Pole	Produktreihen	Bemessungsdaten (IEC 60947)			Bestellnummer				
			Betriebsstrom I <sub>e</sub>	Betriebsleistung bei 380-440V						
			AC-21A A	AC-23A kW	AC-3 kW					
Ein-/Ausschalter 90° Schaltwinkel	3 ... 4	H200-C	20	5,5	3,7	<b>H212 - 41 ... - 013M1</b>				
	3 ... 8	H200-A/-D	20	5,5	3,7	<b>H216 - 41 ... - 013M1</b>				
			25	7,5	5,5	<b>H220 - 41 ... - 013M1</b>				
			32	11	7,5	<b>H226 - 41 ... - 013M1</b>				
			40	15	11	<b>H233 - 41 ... - 013M1</b>				
3 ... 4	H200-B	63	22	18,5	<b>H263 - 41 ... - 013M1</b>					
Umschalter mit Nullstellung 90° Schaltwinkel	3 ... 4	H200-E	20	5,5	3,7	<b>H216 - 71 ... - 013M1</b>				
			25	7,5	5,5	<b>H220 - 71 ... - 013M1</b>				
			32	11	7,5	<b>H226 - 71 ... - 013M1</b>				
			40	15	11	<b>H233 - 71 ... - 013M1</b>				
<b>SMD-Module zum Grundschaltermodul A02</b>										
Bauformmodul für Bauform 013M1			H200-A H200-B/-C/-D/-E		<b>BFA2 - 013</b> <b>BFB2 - 013</b>					
M-Antriebsmodul 64 x 64 mm für Bauform 013M1 Frontschild schwarz, Griff schwarz			H200-A/-B/-C/-D/-E		<b>4AM1</b>					
Schrifteinlage silber für Antriebsmodul 013M1					<b>FAS4 - 9...</b> (FA-Nummer)					
<b>Abmessungen in mm</b>										
Produktreihen	A	B	B1	B2	C	C1	D1	D2	E	H
H200-A	64	36	48	60	58	39	15	5	48	70
H200-B	64	50	69	88	58	39	15	5	48	72
H200-C	64	45	-	-	50	39	15	5	48	45
H200-D	64	72	84	96	66	39	15	5	48	70
H200-E	64	72	84	96	66	39	15	5	48	70